stryker

- BAR EA

LD304 Birthing Bed Your Partner in Delivery

Making mom feel at home, the

LD304 birthing bed provides comfort and security for both the mother and caregiver. Simple operation, mobility and an ergonomic design provide safety while positioning to mom's comfort.



Convenient controls, such as singlebutton Trendelenburg and the Stryker powered Skoocher feature, allow customized positioning with minimal effort.



The ergonomic design of the Stryker foot section promotes proper body mechanics to help protect you from back strain and injury. Patented Lock-Rite[®] foot section glides off for quick and easy breakdown

Length-adjustable footrests provide multiple leg positioning capabilities

Ultra-comfort mattress with integrated, high-memory egg crate topper promotes comfort

Patented Skoocher[®] feature moves mom closer to the perineal edge of the bed with the touch of a button

strvker

3800 E. Centre Ave. Portage, MI 49002 U.S.A. t: 269 329 2100 f: 866 795 2233 toll free: 800 327 0770

www.stryker.com



Standard Features

- Lock-Rite slide-off foot section
- Lightweight, self-standing foot section

LD304 Birthing Bed

- Glideaway foot supports with six-way adjustability
- Single-button Trend.
- Three-position siderails
- In-rail motion controls with lockout
- 17.5-inch (44 cm) low bed height
- 5-inch (13 cm) Ultra Comfort head and seat mattress
- 3-inch (8 cm) foot mattress
- 6-inch (15 cm) Omni Surface[™] casters with wheel covers
- Locking-caster steering
- Four-wheel, steel-ring brake system
 with centrally located activation pedal
- 33-inch (84 cm) mattress width with four motor functions (head, bed, foot, Trend.)
- Automatic pelvic tilt
- CPR release
- Manual backup
- Self-storing handgrips
- Plastic fluid basin
- Under-bed night light
- Wood headboard
- Permanent folding three-stage IV pole
- Two year parts and labor warranty

Optional Features

- Patented Skoocher adjusts seat depth from 12.5 inches to 8.5 inches (32 cm to 22 cm)
- Choice of removable or permanent calf supports
- Lumbar pillow and seat pillow
- Mattress overlay
- Basin liners
- Wallsaver[™] quick-release connecting kit
- Siderail communications includes nurse call only or nurse call with speaker, TV, radio, volume, room/read lights
- Smart TV includes channel up/down, mute
- Pendant control
- Pendant port
- 8-inch (20 cm) casters
- Labor bar
- Linen for head and foot mattresses
- Extended warranty

Specifications

| Model Number | 4701 (International 4701 model has 230 volt option) |
|--|---|
| Overall Length | 93" (236 cm) |
| Overall Width | |
| Siderails Up | 41" (104 cm) |
| Siderails Down | 37" (94 cm) |
| Lift Capacity | |
| Bed | 500 lb. (228 cm) |
| Head Section | 250 lb. (114 cm) |
| Foot Section | 300 lb. (136 cm) |
| Height Range (to litter top) | |
| High | 35.5" (90 cm) |
| Low | 17.5" (44 cm) |
| Litter Positioning | |
| Backrest | 0° – 70° |
| Pelvic Tilt | 4° |
| Maximum Trend. | 8° |
| Patient Surface | 33" x 81" (84 x 206 cm) |
| Mattress Thickness | |
| Head/Seat | 5" (13 cm) |
| Foot | 3" (8 cm) |
| Seat Depth | |
| Standard | 12.5" (32 cm) |
| With Skoocher | 2.5" - 8.5" (32 - 22 cm) |
| Caster Diameter | |
| Standard | 6" (15 cm) |
| Optional | 8" (20 cm) |
| Seat Depth Standard With Skoocher Caster Diameter Standard | 12.5" (32 cm) 2.5" - 8.5" (32 - 22 cm) 6" (15 cm) |

Electronics

| Agency Approvals | C-US UL (120 V AC), CE (230 V AC) | |
|---------------------|---|--|
| Volts | 120 V AC (Domestic) / 230 VAC (International) | |
| Ampere Rating | 10 A | |
| Current Leakage | < 300 microamperes | |
| Frequency | 60 Hz (Domestic) / 50/60 Hz (International) | |
| Hospital Grade Plug | Yes | |
| EMC Compatible | Yes | |
| Motor Function | Bed, head, foot, Trend., Skoocher (optional) | |
| | | |

Stryker reserves the right to change specifications without notice.