

Prime Series® Stretchers

Mobile.
Safe.
Efficient.



Extraordinarily mobile and user-friendly,

the Stryker Prime Series stretchers are designed to reduce the physical strain on clinicians, drive efficiency, and enhance patient comfort. Options such as the Zoom® Motorized Drive System or Big Wheel® Advanced Mobility make transporting heavy patients easier, while electric functionality allows patients to adjust their own position without calling a caregiver for assistance. Fully equipped and highly configurable, Stryker Prime Series stretchers allow you to create the ideal solution to meet your specific needs



Zoom Motorized Drive System on the Stryker Prime stretcher virtually eliminates manual pushing.



Lift Assist® Backrest uses a drop-seat design which uses the patient's weight to help raise the head of the bed while cradling the patient to help reduce boosting.



Electric functionality includes the ability to give patients control of their own comfort, while Chaperone® Stretcher Exit System helps reduce flight and fall risk.

Advanced mobility, with optional Big Wheel or Zoom Motorized Drive System, helps make transport safer and more efficient.

Electric-powered base and litter option makes positioning the stretcher and patient as simple as pressing a button.

Industry's first stretcher exit system alerts the nurse to a potential patient fall.

Optional integrated scale system provides repeatable patient weights.

Pioneer® mattress offers superior pressure redistribution and comfort as a component of preventative skin care.

Power-washable* design with 700 lb. capacity.

Stryker Prime Series



1105

Standard Features

- Thermoformed ABS base with extra capacity storage tray
- 700 lb. weight capacity
- Less than 21-inch low height
- Integrated utility tray
- Litter-mounted oxygen bottle holder
- Integrated transfer board
- Power-washable design (1105 and 1115 only)
- Four-wheel, center-locking brake system with dual end activators
- Dual, side-mounted foot control hydraulics with uni-lower pedal
- Glideaway™ Siderails
- 4 integrated IV receptacles
- +/- Trendelenburg
- 8-inch Omni Surface™ Casters with integrated wheel covers
- Pneumatic backrest/stationary foot
- Constant descent hydraulics
- Dual end brake/steer controls
- 2-year warranty

1105: All Standard Features Plus

- Fifth Wheel Mobility

1115: All Standard Features Plus

- Big Wheel Advanced Mobility

1125: All Standard Features Plus

- Zoom Motorized Drive system

Optional Features

- 4-inch (10 cm) Enhanced Comfort Mattress
- 4-inch (10 cm) or 5-inch (13 cm) Ultra Comfort Mattress
- Pioneer Pressure Redistribution Mattress
- Four-sided brake and steer controls (1105 and 1115 only)
- Pop-up push handles (1105 and 1115 only)
- Knee Assist™ No-crank Hydraulic Knee Gatch
- Exclusive Lift Assist Backrest design with drop seat
- Integrated scale system
- Three-sided hydraulic controls (1105 and 1115 only)
- Defibrillator tray
- Defibrillator tray/foot extender/charting surface
- Dual-ended siderail release
- Footboard/chartholder
- IV caddy
- IV poles (permanent, folding two- or three-stage)
- Serving tray
- Serving tray holder/footboard
- Siderail pads
- Upright oxygen bottle holder
- Restraint straps
- Retractable cord reel (1125 only)



1115

Specifications

	26-inch Litter	30-inch Litter
Model Number	CE 1105 (With Fifth Wheel Mobility) CE 1115 (With Big Wheel Advanced Mobility) CE 1125 (With Zoom Motorized Drive system)	CE 1105 (with Fifth Wheel Mobility) CE 1115 (with Big Wheel Advanced Mobility) CE 1125 (with Zoom Motorized Drive system)
Overall Length		
(1105 and 1115)	85" (216 cm)	85" (216 cm)
(1125)	86" (218 cm)	86" (218 cm)
Overall Width		
Siderails Up	34" (86.4 cm)	38" (96.5 cm)
Siderails Down (1105 and 1115)	30.25" (76.8 cm)	30.5" (77.5 cm)
Siderails Down (1125)	30.25" (76.8 cm)	31" (78.7 cm)
Patient Surface	26" x 75.25" (66 x 191 cm)	30" x 75.25" (76 x 191 cm)
Weight Capacity	700 lb. (318 kg)	700 lb. (318 kg)
Height Range		
High	34" (86.4 cm)	34" (86.4 cm)
Low (1105 and 1115)	20.75" (53 cm)	20.75" (53 cm)
Low (1125)	23" (58 cm)	23" (58 cm)
Litter Positioning		
Backrest	0°–90°	0°–90°
Knee Gatch	0°–40°	0°–40°
Trend./Reverse Trend. (1105 and 1115)	±17°	±17°
Trend./Reverse Trend. (1125)	±16°	±16°
Siderails	14" x 57.75" (36 x 147 cm)	14" x 57.75" (36 x 147 cm)
Caster Diameter	8" (20 cm)	8" (20 cm)
EMC	IEC 60601-1-2	

Warranty

Two years parts, labor and travel

Electric Functionality

- Electric option (only 30 inches wide)
- Electric patient controls
- Foot end nursing controls
- Powered lift (1105 and 1115 only)
- Chaperone Stretcher Exit System
- 120V or 240V available

Stryker reserves the right to change specifications without notice.