

Una Autoclave rápida, confiable y segura para esterilizar cualquier material normalmente procesado con autoclave, en laboratorios, hospitales, clínicas, industrias, etc. Su tapa de desplazamiento lateral puede ser abierta con gran facilidad.

Modelos automáticos con óptimas condiciones de esterilización, temperatura controlada con un alto grado de precisión de 100 °C a 130 °C, por un control digital microcontrolado y sensor PT100 con capacidad para almacenar cuatro programas de esterilización, pantalla LCD para observar temperatura y presión de operación, temperatura programada, tiempo de ciclo, estado del proceso, gráfica P vs t, gráfica T vs t y opción a seleccionar dos niveles de usuario. Resolución de 1 °C.

## CARACTERISTICAS

- Alarmas para límites alto y bajo de temperatura, detección de fallas, bajas de voltaje.
- Timer hasta 99.59 minutos, selección de idioma y unidades de operación.
- Impresora térmica opcional, comunicación digital RS232.
- Manómetro de carátula y doble sistema de seguridad.
- Elementos calefactores, tanque y canastillas en acero inoxidable 304.
- Modelos manuales con control y temperatura máxima de 125 °C.



## AUTOCLAVE

STERILIZER

MODELO	MANUAL		AUTOMATICO				
	FE-396	FE-397	FE-398	FE-399	FE-405	FE-406	
TEMPERATURA MAX. °C	125°	125°	130°	130°	130°	130°	
CONTROL	Manual	Manual	Digital	Digital	Digital	Digital	
PRESION MAXIMA Kg/cm	1.6	1.6	1.9	1.9	1.9	1.9	
TIMER	No	No	99	99	99	99	
POTENCIA W	2000	3000	2000	3000	4000	6000	
VOLTAJE V	120	220	120	220	120	220	220
CORRIENTE A	16	9	25	14	16	9	18
*DIMENSIONES INT. cm	25 x 50		30 x 60		25 x 50		40 x 70
**DIMENSIONES EXT. cm	60x35x100		66x40x101		60x35x100		50 x 80
CAPACIDAD l	24		40		24		90
PESO Kg	47		62		50		160
	65		105		138		

\*(diámetro x altura) (diameter x height)

\*\*(ancho x profundidad x alto) (w x d x h)

Fast, safe and extremely low cost. It sterilizes any material normally processed by autoclaving in hospitals, labs, clinics, nursing homes and industries. The sliding type sterilizer lid can be opened and closed with ease by a simple twist in the handle.

Automatic models with optimum sterilization conditions because the temperature is controller with a high grade of precision from 100 to 130 °C. With a microcontroller digital control and PT 100 sensor, with storage capacity for four sterilization programs, graphic LCD display to monitor operating temperature and pressure, programmed temperature, cycle time, process status, graph P vs t and graph T vs t. Resolution 1 °C.

## FEATURES

- Alarms for high and low temperature safe settings, abnormalities and low volts.
- Timer to 99.59 minutes, language and operation units selection.
- RS232 digital communications, optional printer.
- Stainless steel cover, tank, lid and heating elements.
- Manual models with control and maximum temperature 125 °C.

