

# S360 / S360S Slit Lamp



#### **Features**

Microscope Type: Gaglilean Type

**Maginification Chance:** Revolving Drum (5 or 3 steps)

**Total Maginification:** 6X, 10X, 16X, 25X, 40X (S360); 10X, 16X, 25X (S360S)

Eyepieces: 12.5X

Angle between Eyepieces: 13° Pupilary Adjustment: 52mm-78mm

Diopter Adjustment: +/- 6D

Field of View: ø34.7mm, ø22mm, ø13.5mm, ø8.5mm, ø5.5mm (S360), ø22mm, ø13.5mm, ø8.5 (S360S)

#### Slit Illumination

Slit Width: 0~14mm

Slit Length: 1~14mm continuous

Aperture Diameters: ø14mm, ø10mm, ø5mm, ø3mm, ø2mm, ø1mm, ø0.2mm

Slit Angle: 0°~180°

**Slit Inclination:** 5°, 10°, 15°, 20°

Filters: Heat-absorbing filter, ND Filter, Red-free filter, Cobalt Blue Filter

**Lamp:** 3V LED Module (S360/S360S) **Luminance:** ≥ 60KLX (S360/S360S)

#### **Instrument Base**

Lateral Movement: 110mm

Vertical Movement: 30mm

Fine Base Movement: 15mm

#### Chin Rest

Vertical Movement: 80mm

Fixation: | FD

### **Power Supply**

Input Voltage: 220V/220V~+/-10% Input Frequency: 50Hz/60Hz

Power Consumption: 10VA (max) (S360/S360S)

Output Voltage: Lamp 6V, Fixation 3V

## **Packaging**

Dimension: 770mm x 470mm x 570mm (L/W/H)

Gross weight: 24kg Net weight: 16kg



Stallion Medical Inc.

Addres: 3085 Beyer Blvd. Suite A-105, San Diego, CA. 92154

Phone (619) 428-6320 • Fax (619) 428-6323

E-mail: sales@stallionmed.com

Síganos en:



www.stallion-medical.com

